

> PELI™ LIGHTING INSTRUMENTS FOR BATTLEFIELD CONDITIONS.

LED LIGHTING WITH NO QUIT

Introducing the new Peli™ LED Series. The most efficient and durable torches in the Peli™ line. Up to 10,000 hours of light - and no filament to break. Plus, LEDs consume very low energy, delivering up to 15 times the burn time compared to incandescent bulbs.



Peli™ offers a clean, even pre-focused beam

Other torches offer poor and uneven beams with shadows



NEW M6 also available in 3 Watt version (Ref. 2390).




Peli™ Lights have more safety approvals than any other manufacturer.

PRESERVE NIGHT VISION

Peli™ night vision torches use blue or red lenses to alter the color spectrum and cut the brightness to protect your position and preserve night vision. The infrared lens is used to filter out all other light spectrums for NVG compatibility.

Night vision has revolutionized warfare. Peli's M6 light filters support your tactical advantage. Flexible material provides a sure fit over the M6 lens shroud. A spring loaded lens instantly flips up for full intensity light or locks down to filter the beam.



VB3 for NV use



Ref. 2325

LIGHT MOUNT SYSTEMS

The aluminum M6 Lithium and M6 LED from Peli™ are the top notch tactical torches in the field. Partner them with our Tactical Light Mount System for several models of rifles and you have got the ultimate tool in military operations.

The 610 Front Sight and the 620 Side Sling let you mount your M6 to either side without sight interference. The 630 Foregrip attaches underneath the foregrip using the included picatinny rail. Each system comes complete with hardware for quick installation and a 15 cm remote pressure switch.



610



620



630

DISTRIBUTED BY:

UNCONDITIONALLY GUARANTEED ... FOREVER

All the products contained on this catalogue are covered under the Unconditional Guarantee offered by Peli. This means that if for any reason you are not satisfied with the quality or performance of any product we will gladly replace it or refund your money. Peli will guarantee the product against breakage or defects in workmanship, with no limit of time, as long as instructions have been followed by the user. This guarantee does not cover accessories such as lamps, batteries or case contents. The o-rings must be kept greased (and should be changed if damaged) following the instructions of the product. This guarantee is not valid only if there has been an abusive use of the product, exceeding logical limits. This guarantee does not cover sharkbite, bear attack or children under 5.

LIGHT SPECIFICATIONS AND FEATURES

Ref.	Batteries	Tested Lumen Value	Watts	Battery (hours)	Colours	ATEX Approvals
1900	2 Aik. "AAA"	7	1,11	2	●●●●○	II 3 GD EEx nL IIC T4
1930	4 LR44	8,9	0,18	130	●●	-
2000	3 Aik. "C"	33	3,33	4,5	●●●	II 3 GD EEx nL IIC T4
2130	2 Aik. Coin	4,7	0,3	130	●●	II 3 G EEx nL IIC T6
2220	2 CR2032 Lithium	5,5	0,6	100	●●●	II 2 G EEx ib IIC T6
2270	2 Aik. "AA"	8	1,8	4,5	●●●	II 3 G EEx nL IIC T4
2320	2 CR123 Lithium	74	7,8	1	●●●	-
2330	2 CR123 Lithium	41	1	40	●●●	-
2340	2 Aik. "AA"	8	1,8	4,2	●●●	II 3 G EEx nL IIC T4
2400	4 Aik. "AA"	25	3,18	4	●●●	II 3 GD EEx nL IIC T4
2620	3 Aik. "AAA"	14/9**	1,53/0,41**	2-3/80**	●●●	II 3 G EEx nL IIC T3X
2630	3 Aik. "AA"	7/15/30**	1/1/1**	24/10/3**	●●●	Pending
2640	4 Aik. "AA"	21/9**	3,48/0,54**	3/50**	●●●	II 3 G EEx nL IIC T3X
3310	1 Lithium CR123	26	1	3	●●●	-
3370	3 Lithium CR123	56	3	6,7	●●●	-
3600	4 Aik. "AA"	25	3,18	4	●●●	II 3 GD EEx nL IIC T4
3650	4 NiCad "AA"	28	2,64	1,5	●●●	II 3 GD EEx nL IIC T4
8030	3 Aik. "C"	25	3,42	5-6	●●●	II 3 G EEx nL IIC T3
8050	4 NiCad "C"	151	9,12	1,6	●●●	-
2140	2 Aik. "AAA"	8	1,2	2,5	●●●	II 3 G EEx nL IIC T5
2250	2 Aik. "AA"	7	1,8	5-6	●●●	II 3 G EEx nL IIC T4
2300	2 Aik. "AA"	8	1,8	4,2	●●●	II 3 GD EEx nL IIC T4
1800	2 Aik. "C"	15	2,22	7,5	●●●	II 3 GD EEx nL IIC T4
1820	2 Aik. "C"	15	2,22	7,5	●●●	II 3 G EEx nL IIC T5
2420	4 Aik. "AA"	31,5	3,66	3,5	●●●	II 2 G EEx ia e IIB T3
2450	4 NiCad "AA"	28	2,64	1,5	●●●	II 3 GD EEx nL IIC T4
2430	4 Aik. "AA"	32	3,66	3,5	●●●	II 2 G EEx ib e IIB T3
2600	4 Aik. "AA"	25	4,5/3*	3/5*	●●●	II 3 GD EEx nL IIC T4
7050	3 NiCad "C"	122	7,84	1,25	●●●	II 3 G EEx nL IIC T1
8040	4 Aik. "C"	72	4,8	7,7	●●●	II 3 G EEx nL IIC T3
8150	4 NiCad "C"	151	9,12	1,6	●●●	-
1830	3 Aik. "AAA"	8	0,68	50	●●●	Pending
1890	3 Aik. N-Cells	4	0,9	150	●●●	II 3 G EEx nL IIC T5
2010	3 Aik. "C"	32	1,00	50	●●●	II 3 GD EEx nL IIC T4
2020	3 Aik. "C"	35	1,00	6	●●●	II 3 GD EEx nL IIC T5
2410	4 Aik. "AA"	32	1	32	●●●	II 3 GD EEx nL IIC T4
2460	4 NiMH "AA"	28	1	35	●●●	II 3 GD EEx nL IIC T4
2610	3 Aik. "AAA"	3/9**	0,14/0,41**	150/80**	●●●	II 2 G EEx ia IIB T4
2660	4 Aik. "D"	44/9**	5,76/0,54**	15/400**	●●●	II 3 G EEx nL IIC T3X
2880	4 Aik. "AA"	33	1	33	●●●	Pending
3610	4 Aik. "AA"	32	1	32	●●●	II 3 GD EEx nL IIC T4
3660	4 NiMH "AA"	28	1	35	●●●	II 3 GD EEx nL IIC T4
8020	3 Aik. "C"	35	1	6	●●●	II 3 G EEx nL IIC T5
3700	4 Aik. "C"	48/18*	7,2/4,5*	3,5/4*	●●●	II 3 G EEx nL IIC T4
3750	4 NiCad "C"	72/18*	8,2/3,6*	2,25/4,5*	●●●	II 3 G EEx nL IIC T2
3800	6 Aik. "D"	200	8	6/12*	●●●	Pending
3850	6 NiCad "D"	600/290*	24/11*	1,25/2,5*	●●●	Pending
6000	4 Aik. "D"	125,7	7	10-12	●●●	II 3 GD EEx nL IIC T2
6050	7 NiCad "C"	165	9,83	2	●●●	-
4100	8 Aik. "D"	251,4	14,4	10-12	●●●	-
4200	4 Aik. "C"	112	6,9	3,5	●●●	-
4300	8 Aik. "C"	276	13,8	3,5	●●●	-

*Primary/Back-up light **Brightness: low/medium/high

For inquiry on approvals and product colours, please visit our website at www.peli.com.

PELI PRODUCTS, S.A.
C/ Casp, 33-B, Pral. • 08010 • Barcelona, Spain
TEL 34 93 467 4999 • FAX 34 93 487 7393

PELICAN PRODUCTS, Inc.
23215 Early Avenue • Torrance, CA 90505
TEL 310.326.4700 • 800.473.5422 • FAX 310.326.3311

All trademarks and logos displayed herein are registered and unregistered trademarks of Pelican Products, Inc. and others. Xenon is a registered trademark of General Electric Company. Peli Products, S.A. 2005. Code 0030-076-000E



> MILITARY WATERTIGHT PROTECTOR CASES



MILITARY BEST SELLERS

1900 MityLite™ 1900
1930 L1 1930 LED
1935B Finger Light
1900NVG MityLite™ 1900
2000 SabreLite™ 2000
2130 Mini Flasher™ 2130 LED
2130IR Mini Flasher™ 2130 LED
2220 VB3 2220 LED
2220BNV VB3™ NV LED
2270 VersaBrite™ 2270
2270BNV VersaBrite™ II
2320 M6 2320
2330 M6 2330 LED
Filter cap 2325 Red, 2325 Blue, 2325 IR
Filter cap 2325 Red, 2325 Blue, 2325 IR

MILITARY BEST SELLERS

2340 MityLite™ 2340
2340BNV MityLite™ 2340
2390 M6 2390 LED 3W (OD Green)
2400 StealthLite™ 2400
2400CNV StealthLite™ 2400
2620 HeadsUP Lite™ 2620
2620CNV HeadsUP Lite™ 2620
2630 HeadsUP Lite 2630 LED
2640 HeadsUP Lite™ 2640
Filter cap 2325 Red, 2325 Blue, 2325 IR
Filter cap 2325 Red, 2325 Blue, 2325 IR

MILITARY BEST SELLERS

3310 M1 3310
3370 M3 3370 (OD Green)
3600 Little Ed™ 3600
3650 Little Ed™ Rechargeable 3650
8030 M8 8030
8030BNV M8 8030
8050 M11 Rechargeable 8050
Filter cap 2325 Red, 2325 Blue, 2325 IR
Filter cap 2325 Red, 2325 Blue, 2325 IR

PERSONAL LIGHTS

2140 Tracker 2140
2250 VersaBrite™
2300 MityLite™ 2300
1800 Pelilite™ 1800
1820 Pocket Sabre™ 1820
2450 StealthLite™ Rechargeable 2450
2420 MityLite™ 2420
2430 MityLite™ 2430
2600 HeadsUP Lite™ 2600

LIGHT KITS

1950 Mini System
1940 L1 LED Knife/Lite Combo
1980 Knife/Lite Combo

LED AND RECOIL™ SERIES

1830 L4 1830 LED
1990 MityLite™ 1990 LED
2010 SabreLite™ 2010 Recoil™ LED
2020 SabreLite™ 2020 Recoil™ LED
2410 StealthLite™ 2410 Recoil™ LED
2460 StealthLite™ Rechargeable 2460 Recoil LED
2610 HeadsUP Lite™ 2610 LED
2660 HeadsUP Lite™ 2660 LED

LED AND RECOIL™ SERIES

2680 HeadsUP Lite™ 2680 Recoil LED
3610 Little Ed™ 3610 Recoil LED
3660 Little Ed™ Rechargeable 3660 Recoil LED
8020 M8 8020 Recoil LED

HEAVY DUTY LIGHTS

6000 LaserPro™ 6000
6050 M13 Rechargeable 6050

BLACK KNIGHT SERIES

8040 M10 8040
8150 M12 Rechargeable 8150

SPECIALTY LIGHTS

3750 Big Ed™ Rechargeable 3750
3700 Big Ed™ 3700
3800 Big D™ 3800
3850 Big D™ Rechargeable 3850

PRIMARY DIVE LIGHTS

4100 Aqua KingLite™ 4100
4200 Nemo™ 4200
4300 Nemo™ 4300

Submersible Rechargeable LED Series

